

are you press ready?

File Specification Checklist

- For best results** files should be built in CMYK mode
RGB and LAB color builds can cause drastic color shifts
- All images should be CMYK and high-resolution
Recommended 300 dpi (and not scaled up or down more than 20%)
- If they must be used,**
 - Bitmap images (.bmp) should be a minimum of 800 dpi
 - Portable network graphics (.png) must be a minimum of 300 dpi
- Black solids** should be built as “Rich Black” 60 / 40 / 40 / 100
Black text should use “Black” 0 / 0 / 0 / 100
- When providing PDF’s,** export as Acrobat 7 (PDF 1.6) or higher and turn on bleeds and marks
- PDF files for print must be CMYK, high resolution, print quality, in correct page order, with all fonts embedded and with bleeds
- All files should have at least 1/8 (0.125) inch bleed
- Submitted files should include all NOT TO PRINT items** (perforations, scores, folds, dielines, FPO) as Spot colors as list in our [Die Line Legend](#)
- When sending open application files,** include all fonts used—
printer and screen fonts plus fonts used in any images, then zip packaged folder before uploading to FTP site
Include fonts with InDesign’s “Package” or Quark’s “Collect for Output”.
- All files sent should include some sort of proof (lasers, PDF, etc.)



miles

49223 West 78th Street
Indianapolis, IN 46268
317.870.6115

MilesPrinting.com